


Multi-Point Astragal

Secure performance for your door system.



Deflection: Typical french door installations only hold the active door at one point: the deadbolt. This assembly allows for door panel deflection, air and water infiltration.



The Multi-Point features patent pending lock pawls activated by the deadbolt to engage keepers in the active door, providing three locking points. No deflection.

Endura's Multipoint Astragal combines the strength and support of a multi-point lock with Endura's Ultimate Astragal to provide:

- **Solid protection against deflection** in fiberglass, wood or wood-edge steel doors—three secure locking points stop air and water infiltration, save energy.
- **Cost effectiveness**—save on both hardware costs and labor.
- **Ease of installation**—minimal machining and the simplicity of installing or retrofitting an astragal.
- **Works with most standard deadbolt lock sets**—no special hardware.
- **All the features of the Ultimate Astragal**—patented floating boot, simple solution corner pad, aluminum body and 4-way adjustable strike.
- **Availability in both standard and veneer finishes.**
- **Flip-Lever standard**—enhanced accessibility.

The information contained in this document is the confidential and proprietary information and trade secrets of Endura Products, Inc. Any disclosure, use or dissemination of such information without the express written permission of Endura Products, Inc. is strictly prohibited. Endura Products, Inc. also owns any and all intellectual property rights embodied in such information, including patent rights, copyrights, and trademark rights, and no license of any intellectual property right is intended, nor should any license be implied, as a result of the receipt of this document.

U.S. Patents: 5, 426, 894; 6, 789, 358; 7, 350, 336; 5, 588, 266; 5, 611, 173, D354, 572 Other patents pending



PERFORMANCE STANDARD

8817 W. Market St., Colfax, NC 27235
1.800.334.2006 www.enduraproducts.com

A one-two punch for secure performance

The flip lever activates both flush bolts and the floating boot at the same time. Engaging the deadbolt activates both lock pawls into keepers. Secure Performance Standard.



1. Activate Flip Lever, Engage Floating Boot
Operate Flip-Lever to engage both flush bolts and patented Floating Boot at once.



Patented spring loaded Floating Boot finds the lowest point on the sill that maintains a perfect seal at all times.



2. Engage deadbolt, activate Multi-Point Lock Engaging the deadbolt compresses the lock actuator to activate the patented locking system.



Upper and lower multi-point lock pawls are captured by keepers in the active door panel.

Certified Testing

Performance of the Ultimate Multipoint Astragal was validated by certified testing through an independent, accredited laboratory. The following test protocols were utilized to verify performance: Air penetration resistance per ASTM E 283; Water penetration resistance performance per ASTM E 547; and Structural performance per ASTM E 330.

Endura Multi-Point Astragal 6/8 Certified Testing Result						Endura Multi-Point Astragal 8/0 Certified Testing Result					
6/8 Inswing						8/0 Inswing					
Manufacturer/Brand	Panel Type	Glass Type	Air	Water	Structural	Manufacturer	Panel Type	Glass Type	Air	Water	Structural
JELD-WEN® Energy Saver®	Steel	Insert	0.03	DP40	DP45	JELD-WEN® Energy Saver®	Steel	Insert	0.05	DP40	DP45
JELD-WEN® Energy Saver®	Fiberglass	Insert	0.05	DP35	DP40	JELD-WEN® Energy Saver®	Fiberglass	Insert	0.03	DP30	DP40
Masonite® Bellville® Smooth	Fiberglass	Flush	0.02	DP40	DP55	Masonite® Bellville® Smooth	Fiberglass	Flush	0.03	DP35	DP+40/-45
Masonite® Bellville® Smooth	Fiberglass	Insert	0.03	DP35	DP45	Masonite® Bellville® Smooth	Fiberglass	Insert	0.01	DP35	DP40
Masonite® Masonite® HD	Steel	Insert	0.03	DP45	DP50	Masonite® Masonite® HD	Steel	Insert	0.03	DP45	DP+40/-45
Plastpro® Select Fiberglass	Fiberglass	Flush	0.03	DP45	DP55	Plastpro® Select Fiberglass	Fiberglass	Flush	0.04	DP35	DP40
Plastpro® Select Fiberglass	Fiberglass	Insert	0.04	DP40	DP45	Plastpro® Select Fiberglass	Fiberglass	Insert	0.03	DP35	DP35
Therma-Tru® Fiber Classic®	Fiberglass	Flush	0.05	DP40	DP+45/-50	Therma-Tru® Fiber Classic®	Fiberglass	Flush	0.05	DP40	DP+45/-50

Other Testing

In addition to certified testing, the Ultimate Multipoint Astragal operation and durability were successfully evaluated based on additional industry standards. These include:

Bolt Operating Lever and Bolt Durability – The bolt lever, engagement bolts, and associated mechanisms were operated for 300,000 cycles (based on BHMA A156.5, Grade 2).


Deadbolt Actuator and Multipoint Latch Durability – The deadbolt actuator, multipoint latches, and associated mechanisms were operated for 300,000 cycles (based on BHMA A156.5, Dead Lock Grade 2).

Salt Spray Resistance – All components were exposed to a salt fog under elevated temperatures for 1,000 hours (per ASTM B 117).

Veneer Finishes



Aluminum Body Colors



The information contained in this document is the confidential and proprietary information and trade secrets of Endura Products, Inc. Any disclosure, use or dissemination of such information without the express written permission of Endura Products, Inc. is strictly prohibited. Endura Products, Inc. also owns any and all intellectual property rights embodied in such information, including patent rights, copyrights, and trademark rights, and no license of any intellectual property right is intended, nor should any license be implied, as a result of the receipt of this document.

U.S. Patents: 5, 426, 894; 6, 789, 358; 7, 350, 336; 5, 588, 266; 5, 611, 173, D354, 572

Other patents pending



PERFORMANCE STANDARD

8817 W. Market St., Colfax, NC 27235
1.800.334.2006 www.enduraproducts.com

Contact us for more information.